

멀티 채널 수신반 (KFI_소방인증)

GTC-210A



Features

- 국제표준인 Din type case가 적용되어 채널 확장이 용이합니다.
- RS-485 Modbus 통신이 가능합니다.
- 상황에 따라 3단 경보 농도를 LED에 표시합니다.
- Relay 접점 출력 기능을 제공합니다.
- 다양한 형태(자립식 판넬형/벽걸이형/19" Rack형)로 구성 가능합니다.
- 가스감지기 GTD-2000Ex와 연계된 KFI 형식 승인 제품입니다.
- 자가진단 기능이 내장되어 있습니다.

Accessories



19" Rack type



Back-up power unit



RS-485 Module

제품 사양

Unit	Common (Alarm Unit)	Channer (Density Indicating Unit)
Operation display	8-LED (Power, 3-stage alarm, Trouble, Buzzer stop, PC & channel data communication)	6-LED (Power, 3-stage alarm, Trouble, Stand-by for maintenance)
Measuring display	-	4-Digit FND & Bar-graph (32 segment, 3-color LED)
Measuring range	-	1~9999 (programmable) (%LEL, ppm, % Vol)
Alarm display	Visual : 3-stage alarm, Trouble LED Audible : buzzer	Visual : 3-stage alarm, Trouble LED
Alarm output signal	3-stage alarm, Trouble, Buzzer AC250V 3A relay contact (SPDT)	3-stage alarm, Trouble, Buzzer AC250V 3A relay contact (SPDT)
Alarm level set	-	Programmable within detection range
Input signal	-	4~20mA DC (2-wire or 3-wire)
Output signal	Isolated RS-485 Communication Modbus (Option)	4~20mA DC
Reset signal	Reset switch and remote control	Reset switch
Program set mode	-	Alarm value (1, 2, 3 alarm) Alarm time (Instant & Delay) 1~30min Alarm dead band Relay output on/off
Operating temperature	-20°C ~ 60°C	
Operating humidity	5 ~ 99% RH (Non-condensing)	
Battery power	Back-Up. power unit (Option) 24V DC / 600mAH, 1300mAH (Option)	

제품 인증

기타 인증	KC	국내 전자파 인증	-
	KFI	국내 소방 인증	